

eX710

10.1" TFT color with multitouch projected capacitive touchscreen. 3 Ethernet ports, 1 serial port, 2 USB ports. JMobile runtime.



- 10.1" TFT color display, resolution 1280x800 pixel, 16M colors. Dimmable LED backlight
- Projected capacitive touchscreen. True glass design. Multitouch operation
- 3 Ethernet ports
- SD Card slot
- 2 Plug-in modules for system expansion

Product overview

eX Series 700 HMI products combine state-of-the-art connectivity features and top performance in a great design. Products have been designed as IoT edge devices with the combination of a powerful controller with networking capability and outstanding communication options including client/server OPC UA. They are the ideal choice for all demanding IoT edge applications in factory, marine and building automation.

The glass projected capacitive touchscreen and the brilliant 10.1" widescreen display with resolution of 1280x800 guarantee great optical performance; with the support of multitouch gesture programming they can create the most natural human interfaces.


eX Series 700 HMI products have been designed to run the JMobile software.

- JMobile runtime included.
- Requires JMobile V2.5 or higher.
- Supports JMcloud secure connectivity with full network separation.
- OPC UA Server and Client.
- Optional CODESYS V3 runtime with choice of EtherCAT, Profinet, Ethernet IP and Powerlink.


Technical Data

Display Type Resolution Active display area Colors Backlight Brightness Dimming	TFT 1280x800, WXGA 10.1" diagonal 16M LED 500 Cd/m ² typ. Dimmable to 0%	Environment Conditions Operating temperature Storage temperature Operating and storage humidity Protection class	-20° to +60 °C (vertical installation) Plug-in modules and USB devices may limit max temperature to +50 °C. -20 to +70 °C 5 – 85 % RH, non-condensing IP66 (front) IP20 (rear)
System Resources CPU Operating System Flash RAM Real Time Clock RTC backup Buzzer	ARM Cortex-A9 dual core 800 MHz Linux RT 4 GB 1 GB Yes Yes, rechargeable battery Yes	Dimensions and weight Faceplate LxH Cutout AxB Depth D+T Weight	282x197 mm (11.10x7.80") 271x186 mm (10.67x7.32") 56+8 mm (2.20+0.33") 1.7 Kg
Operator Interface Touchscreen LED indicators	Projected capacitive Multitouch, 2-points gestures -	Approvals CE	Emission EN 61000-6-4 Immunity EN 61000-6-2 for installation in industrial environments
Interface Ethernet port 0 Ethernet port 1 Ethernet port 2 USB port 1 USB port 2 Serial port 1 SD card Expansion	10/100/1000 10/100 10/100 Host V2.0, max. 500 mA Host V2.0, max. 500 mA RS-232, RS-485, RS-422, software configurable. Max 3 serial ports using plug-in modules. Yes 2 slots for plug-in modules		
Ratings Power supply voltage Current consumption Input protection Battery	24 Vdc (10 to 32 Vdc) 1.0 A at 24 Vdc (max.) Electronic Rechargeable Lithium battery, not user-replaceable		

Dimensions



Connections



Ordering Information

Model	Part Number	Description
eX710	+EX710U5P1	10.1" widescreen TFT color with multitouch projected capacitive touchscreen. 3 Ethernet ports, 1 serial port, 2 USB ports. JMobile runtime.

ptn0591

Ver. 1.1

Copyright © 2016 EXOR International S.p.A. – Verona, Italy

Subject to change without notice

The information contained in this document is provided for informational purposes only. While efforts were made to verify the accuracy of the information contained in this documentation, it is provided "as is" without warranty of any kind.

www.exorint.com